

TABELA NR1/11																			
Lp.	Odcinek	Długość F 90 PE	Długość F 160 PE	Długość F 180PE	Długość F 225 PE	Kubatura wykopu wąsko przestrzenego	Rury ochronne stalowe śr. 273x7,1	Rury ochronne stalowe śr. 324x8,0	Rury ochronne stalowe śr. 356x10									hydranty	Uwagi
					l					TRÓJNIKI				ZASUWY					
										150/80	150/100	150/150	200/200	□ 200	□ 150	□ 100	□80		
		[m]	[m]	[m]	[m]	[m3]	[m]	[m]		szt.	szt.	szt.	szt.	szt.	szt.	szt.	szt.	szt.	
1	191-192				211	379							1	2					
2	192-195a			255		458													
3	195a-195			24		43						1			2				
4	195-196			360		633		8,00										2	
5	196-197			357		642				1					1		1		
6	197-197a		165			275		12,00										1	
7	197a-200		296			533												2	
8	200-ZΦ150		415			693		30,00							1			1	
9	ZF150-201		637			1117		16,00			1				1	1		4	
10	201-202	112				174	15,00												
11	197-198	90				140	12,00											1	OD
12	197A-HP	69				106	10,00										1		
13	195-HP	186				323	7,00											1	
14	192-193				257	448			8,00										
15	193-194				233	420								1				1	
16	194-277				209	376													
17	-	90				140	12											1	
18	-	225				405												1	
19	191-189A				294	511			10					1					